











FlashLink Pro Display Data Logger

MODEL		LCD	VANJSKI SENZOR °C	UNUTRAŠNJI SENZOR °C	ODGODA ALARMA	KAPACITET PODATAKA	FREKVENCIJA ZAPISA	BATERIJA	CERTIFIKAT	SOFTWARE
FlashLink Pro Display Data Logger Model 20269		•	•3m kabel • -40+150		0—79 min	16 110 points	3 sec—24 h	2 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Pro Display Data Logger Model 20268		•	•2m kabel • -40+150		0—79 min	16 110 points	3 sec—24 h	2 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Pro Display Data Logger Model 20261		•		• -40+55	0—79 min	16 110 points	3 sec—24 h	2 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Electronic Data Logger Model 20209			•1m kabel • -40+150		0—79 min	7,918 points	3 sec—24 h	1 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Electronic Data Logge Model 20207				• -40+ 60°C • 1%99% RH	0—79 min	10,339 points	3 sec—24 h	1 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Electronic Data Logge Model 20205			•1m kabel • -80+110		0—79 min	7,918 points	3 sec—24 h	3 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Electronic Data Logge Model 20204			•1m kabel • -40+150 •1m kabel • -40+150		0—79 min	7,918 points	3 sec—24 h	1 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software

MODEL		LCD	VANJSKI SENZOR °C	UNUTRAŠNJI SENZOR °C	ODGODA ALARMA	KAPACITET PODATAKA	FREKVENCIJA ZAPISA	BATERIJA	CERTIFIKAT	SOFTWARE
FlashLink Electronic Data Logger Model 20202			<ul style="list-style-type: none"> • 1m kabel • -40+150 	<ul style="list-style-type: none"> • -40 +150 	0—79 min	7,918 points	3 sec—24 h	1 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
FlashLink Electronic Data Logger Model 20200				<ul style="list-style-type: none"> • -40 +66 	0—79 min	3,822 points	3 sec—24 h	1 god. trajanje	T.U.V. CE Mark	FlashLink Program Manager Software
Jumbo Display Thermo-Hygrometer Model 13307		•	<ul style="list-style-type: none"> • -50+70 	<ul style="list-style-type: none"> • 0 +50 • 20%90% RH 	Uređaj je opremljen s alarmom koji se aktivira na 0 °c. Postoji mogućnost pohranjivanja i prikaza najviših i nanižih izmjerenih vrijednosti.				T.U.V. CE Mark	

